
Lifeboat Safety Infographic



Fully Enclosed Lifeboat Launching from Stowed Position Procedures for Launching in a Safe Atmosphere

(SOLAS Chapter III / Regulation 28)

1 INITIAL ACTIONS

- MAKE SURE HARBOR SECURING PINS ARE REMOVED.
- DISCONNECT POWER CHARGE CABLE.
- CLOSE DRAIN PLUGS.
- PLACE E.P.I.R.B. AND S.A.R.T. ON BOARD.

BOARD WHEN ORDERED





2 ACTIONS FOR LAUNCHING

- RELEASE GRIPES AND SECURING WIRES.
- · SECURE HATCHES.
- IF IN A SAFE ATMOSPHERE: OPEN VENTS.
- IF IN A DANGEROUS ATMOSPHERE: CLOSE VENTS.



3 LOWER TO WATER



- ENSURE THE LAUNCHING AREA IS CLEAR.
- OPERATE BRAKE RELEASE.
- BE AWARE THAT BOAT MAY SWING DURING LAUNCH.
- LOWER BOAT AT A STEADY RATE.



4 ENTERING WATER



- . LET THE BOAT SETTLE IN THE WATER.
- KEEP BRAKE OFF.
- RELEASE FALLS.
- IF FALLS DO NOT OPEN, OPERATE EMERGENCY RELEASE:
 - A) BREAK
- B) MOVE LEVER TO GREEN
- C) RELEASE FALLS



5 LETTING GO







- START ENGINE.
- IF IN A DANGEROUS ATMOSPHERE: A) OPEN AIR SUPPLY.
 B) OPEN WATER SPRAY VALVES.
- WHEN READY RELEASE PAINTER.
- STEER AWAY FROM



6 FINAL ACTIONS





- RESCUE ANY SURVIVORS IF SAFE TO DO
- ONCE CLEAR OF SHIP, STREAM SEA ANCHORS.





DALITE LC1059 Source: https://www.datrex.com/