

# Safety Signs Checklist



The following checklist on the uses of color coding and signs, if checked “okay,” gives a measure of guidance concerning the adequacy of safety signs and visual clues in your operation:

- ☐ Is red used as the basic color to indicate fire, danger, or stop, on emergency stop bars or buttons and fire quenching materials?
- ☐ Is orange used as the basic color to indicate dangerous parts of machines and energized equipment, such as on the inside of movable guards and exposed edges of pulleys or gears?
- ☐ Is yellow used to designate caution and for marking hazards such as falling, tripping, or being caught in between the unguarded edges of platforms and treads of stairways?
- ☐ Is green used as the basic color to designate “Safety” and the location of equipment – i.e. stretchers and first aid kits?
- ☐ Is blue used as the basic color to designate service type measures such as “Notice” signs?
- ☐ Is purple used as the basic color to designate radiation hazards – i.e. containers and storage areas for radioactive materials?
- ☐ Is black, white, or a combination used to designate traffic and housekeeping marking i.e. – location of aisles, passageways, or refuse cans?
- ☐ Is the piping system marked, identified, and color coded according to the latest standards?
- ☐ Are danger signs – red oval with white “Danger” in upper panel and black/white field – used only where an immediate hazard exists?
- ☐ Are caution signs – yellow “Caution” in upper panel and black/yellow field – used only to warn against potential hazards or unsafe practices?
- ☐ Do safety instruction signs such as, “Safety First” and “Think”– have white letters on green field in upper panel – used for general instruction?
- ☐ Are informational signs – white “Notice” on blue field in upper panel – used to advise of general information needs such as directions to offices or other matters of company policy?
- ☐ Are exits marked (exit signs must be 6” high, 3/4” wide and lighted in high visibility contrasting colors)?

- ☐ Are doors which may be confused with exits, marked "No Exit"?
- ☐ Are clearances, safe floor loads, voltage, and smoking prohibition signs posted conspicuously?
- ☐ Are tags—"Danger, Caution, Do Not Start"—used as temporary warnings placed conspicuously on defective equipment, and made to the sign specifications of color and format?
- ☐ Does the location of the sign provide maximum visibility?
- ☐ Is care taken to avoid grouping too many signs in one location?
- ☐ Is the sign well-lit by daylight or illumination?
- ☐ Does the location of the sign alert the viewer at sufficient distance, so the viewer can act correctly?
- ☐ Is the size of the sign determined by the safe alerting distance, not the available space the sign will fit?
- ☐ Is the sign itself a hazard by its placement?
- ☐ Does the type of sign and the sign wording fit the location?
- ☐ Are the signs inspected on a regular basis?
- ☐ Is there a location sheet or master plan indicating where signs are? Is it shown on drawings of the product?
- ☐ Are the signs cleaned and refurbished to maintain visibility?
- ☐ Are the signs replaced or removed when the information is not any longer needed?
- ☐ Are the signs placed in such a way that they are not obscured in any way by columns, posts, or switches on hand tools?